

15mtr MOBILE CONVEYOR (SINGLE AXLE)



FEATURES

- Belt speed 90m/min.
- Easy to set up.
- Can be toed.
- Radial arc movement.

OPTIONS

- Diesel power unit 25KVA generator.
- Hydraulics- Single acting cylinder with hand pump for adjusting degree of inclination.
- · Variable height support stand.
- · Octagonal chute.

SPECIFICATION

- Assy Wt- 3 ton appx.
- Length 15 mtr, width 2.2mtr, Height 6.8mtr.
- Stockpile height 5.5mtr.

COMPONENTS

- Feedboot-900mm x 1300mm.
- Main Conveyor- Belt width 800mm x 15mtrs length.
- Drive unit- 15HP, 4 pole, 3phase, 415V electric motor with shaft mounted gear reducer.
- Chasis- Axle and tyre arrangement, for toeing and radial movement.

APPLICATIONS

- Concrete, mortar and asphalt sands.
- Quarry dust / crushed fines.
- Silica sand for glass industry.
- · Recycled materials .
- Ore.





15mtr/20mtr MOBILE CONVEYOR (DOUBLE AXLE)



COMPONENTS

- Feedboot-900mm x 1300mm
- Main Conveyor- Belt width 800mm x 15mtrs length
- Drive unit- 15HP/20HP, 4 pole, 3phase, 415V electric motor with shaft mounted gear reducer
- Chasis- Axle and tyre arrangement, for toeing and radial movement

APPLICATIONS

- Concrete, mortar and asphalt sands
- Quarry dust / crushed fines
- Silica sand for glass industry
- Recycled materials
- Ore

FEATURES

- Belt speed 90m/min
- Easy to set up
- Can be toed
- Radial Arc movement

OPTIONS

- Diesel power unit 25 KVA/35 KVA Generator
- Hydraulics- Single acting cylinder with hand pump for adjusting degree of inclination
- Variable height support stand
- Octagonal chute

SPECIFICATION

- Assy Wt- 3.5 tons appx
- Length 15 mtr/20 mtr, width 3.3mtr, Height 6.8mtr
- Stockpile height 5.5mtr







391, M. G. Road, Tilakwadi, Belgaum - 590 006.

Mobile: 0 94484 61097 Telefax: 0831-2461097 E-mail: precision.engineers391@gmail.com